Clearflo<sup>®</sup> Ag-47

Clear Antimicrobial Phthalate-Free PVC Tubing





Fluid Transfer Specialists®



# Clearflo® Ag-47.

### Clear Antimicrobial Phthalate-Free PVC Tubing



Made from non-toxic ingredients conforming to FDA standards

- Free of phthalates, latex and animal-derived ingredients
  - Listed by the National Sanitation Foundation (NSF-51) for food equipment materials
    - Antimicrobial ingredient is throughout the tubing, not only on an inside liner as with other products
    - Transparent for visual flow contact
  - Contains antimicrobial technology to guard against bacteria such as E. coli, listeria, salmonella, legionella, MRSA, campylobacter and pseudomonas



Well suited for food and beverage applications including non-fatty aqueous, milk and alcoholic beverages (below 20% ABV)

REACH and RoHS compliant

- Heat sealable

#### Notes

CLEARFLO Ag-47 is suitable for a wide variety of food contact applications and designed to protect your food or beverage product from harmful bacteria. It's manufactured from a clear flexible Shore A74 phthalate-free PVC compound with the addition of antimicrobial protection. The antimicrobial technology is especially effective where there is infrequent use of fluids in warm or humid conditions and the tubing has no opportunity to dry thoroughly between uses.

The antimicrobial properties protect the tubing against organisms that can cause growth-based discoloration and odors. Testing has proven that the active ingredients neutralize bacteria rapidly, and because the ingredients do not dissipate with use, they can be expected to offer protection for an extended time under normal conditions. CLEARFLO Ag-47 offers antibacterial performance to ISO 22196:2011.

Unlike some products CLEARFLO Ag-47 is 100% protected with the effective additive, which is present throughout the tube and not only on a liner, for protection on all surfaces. This is important in applications where the tubing is submerged or dipped into fluid or if any surface of the tubing is cut or becomes compromised. Tubing products that only offer a liner layer of antimicrobial protection risk the liner becoming separated from the cover. If the antimicrobial layer is cut, the tubing under that cut becomes susceptible to bacteria growth. This can often happen at the fitting.

The active ingredients in CLEARFLO Ag-47 will have no detrimental effect on yeasts used for brewing and will have no negative impact on the taste or flavor of products passed through it.

PART NO.	ID (IN.)	OD (IN.)	WALL (IN.)	WORKING PSI AT 70°F	BURST PSI AT 70°F	LBS. PER 100 FT.
1190014	1/8	1/4	1/16	165	497	1.95
1190021	1/8	3/8	1/8	236	709	5.19
1190035	3/16	5/16	1/16	126	379	2.59
1190049	3/16	7/16	1/8	180	540	6.48
1190112	1/4	3/8	1/16	100	301	3.25
1190126	1/4	1/2	1/8	161	482	7.79
1190189	5/16	7/16	1/16	83	248	3.89
1190203	5/16	9/16	1/8	121	364	9.08
1190266	3/8	1/2	1/16	74	223	4.55
1190280	3/8	5/8	1/8	108	324	10.38
1190343	1/2	5/8	1/16	51	154	5.85
1190357	1/2	3/4	1/8	83	249	12.98
1190392	5/8	3/4	1/16	45	136	7.14
1190399	5/8	7/8	1/8	69	209	15.58
1190448	3/4	7/8	1/16	37	111	8.44
1190455	3/4	1	1/8	57	171	18.17
1190497	1	1-1/4	1/8	42	127	23.37

Standard coil length is 100 ft. Add length suffix to part number when ordering. Example: 100 ft. of 3/16" l.D. x 5/16" O.D. tubing is part number 119 0035-100. Sold by standard coil length only.

BOLD indicates the critical dimension for fittings application.

#### **Physical Properties\*\***

Hardness, Shore A ±5	74
Operating Temperature Range, °F	-40 to 125
Operating Temperature Range, °C	-40 to 52

\*\*Values listed are typical for the material used in manufacture, except where noted, and are meant only as a guide to aid in design. Field testing should be performed to find the actual values for your application.

## Recommended Fittings & Clamps

- Thermobarb<sup>®</sup> plastic barbed fittings
- Stainless steel barbed fittings
- Oetiker<sup>®</sup> ear type clamps
- Kwik Clamp<sup>™</sup> nylon double bond hose clamps
- Worm gear clamps

Clearflo, Kwik Clamp, Thermobarb, NewAge, "Fluid Transfer Specialists," and The "N" Logo are trademarks of NewAge® Industries, Inc. • Oetiker reg. TM Oetiker, Inc

WARANT: NewAge Industries, new reget, Fluid Interface Operations, and in the NewAge Industries, new registering. The foreing of the interface of the interface

DISTRIBUTOR PARTNER



145 James Way Southampton, PA 18966 www.newageindustries.com 800-50-NEWAGE (800-506-3924) 215-526-2300 Fax: 800-837-1856 215-526-2190 info@newageindustries.com