

**Tri-Clamp Connection Service Ratings for
304 & 316 SS Connections**

Size OD (in)	Single Pin 13MHHM (psig)		Double Pin 13MHHD (psig)		Heavy Duty 13MHH-H (psig)	
	@ 70°F	@ 250°F	@ 70°F	@ 250°F	@ 70°F	@ 250°F
1/2"	1500	1200	-	-	1500	1200
3/4"	1500	1200	-	-	1500	1200
1"	500	250	500	250	500	250
1-1/2"	500	250	500	250	500	250
2"	450	250	450	250	450	250
2-1/2"	400	200	400	200	400	200
3"	350	150	350	150	350	150
4"	200	125	200	125	200	125
5"	175	100	-	-	175	100
6"	150	75	-	-	150	75
8"	100	50	-	-	100	50
10"	40	30	-	-	40	30
12"	30	25	-	-	30	25

Note: Pressure ratings are based upon hydrostatic tests using Standard Buna-N gaskets with proper joint assembly and the absence of shock pressure. All ratings are dependent upon the proper selection and installation of components

Tri-Clamp Connection Service Ratings for 304 & 316 SS Connections

Size OD (in)	3-Piece 13MHHS (psig)		High Pressure 13MHP (psig)		Snap-Lock EG13 (psig)	
	@ 70°F	@ 250°F	@ 70°F	@ 250°F	@ 70°F	@ 250°F
1/2"	-	-	1500	1200	-	-
3/4"	-	-	1500	1200	-	-
1"	600	300	1500	1200	150	125
1-1/2"	600	300	1500	1200	150	125
2"	550	275	1000	800	150	125
2-1/2"	450	225	1000	800	150	125
3"	350	160	1000	800	150	125
4"	250	150	800	600	150	125
5"	-	-	-	-	-	-
6"	-	-	300	200	-	-
8"	-	-	250	150	-	-
10"	-	-	-	-	-	-
12"	-	-	150	100	-	-

Note: Pressure ratings are based upon hydrostatic tests using Standard Buna-N gaskets with proper joint assembly and the absence of shock pressure. All ratings are dependent upon the proper selection and installation of components